

Eco Variable M(+)

High Efficiency Wet Rotor Circulators



Description

Application : High efficiency circulators for residential heating, cooling and domestic water applications.

This range combines high efficiency, simplicity and reliability in a single cost effective package. Compact and easy to install, all models feature a unique “one turn” knob to set up control modes and speed settings. An interchangeable plug connection, automatic air-purge and a multicolor LED come as standard.

The M+ option includes the above, plus:

- A three-digit digital display that alternates automatically to show power consumption, head and flow rate.
- A communication LED via Bluetooth wireless technology for external monitoring.
- Night mode.
- E-Adapt for automatic set-up of circulator performance to ensure minimum power consumption.

The full range reaches an EEI level ≤ 0.18 . Precision engineered motor and hydraulics maximise efficiency and allow energy savings of up to 80% compared to standard circulators. The EEI level ensures a fast payback on investment.

For sizing advice, please contact our office for assistance.



Specification

Model	15-6/130	20-6/130	25-6/130	25-6/180	32-6/180
Product Code (M)	CPEA4207	CPEA4209	CPEA4210	CPEA4225	CPEA4233
With LED Display (M+)	CPEA4221	CPEA4224	CPEA4260	CPEA4232	CPEA4238
Max Head	6.0 m	6.0 m	6.0 m	6.0 m	6.0 m
Max Flow	50 lpm	50 lpm	50 lpm	50 lpm	50 lpm
Motor Rating	230V	230V	230V	230V	230V
Port Size (F)	R 1.0"	R 1.25"	R 1.5"	R 1.5"	R 2.0"
Length	130 mm	130 mm	130 mm	180 mm	180 mm