

FEATURES / SPECIFICATIONS


- Floor standing close-coupled toilet, Back-to-wall,
- Built-in Macerator pump (400W; 220-240V AC 50Hz; IPX4) with quiet noise level.
- Maximum discharge height: 7m.
- Maximum water temperature: 75°C.
- Flexible 360° pump outlet connector suitable for DN22 or DN32 pipes
- 3 auxiliary inlet connections (right/left/back) for washbasin or other bathroom fittings
- Vitreous china rimless wash down bowl
- Dual-flush: 4,5/3 lpf, Double chrome button activation
- Roca inlet and flush valve
- Cistern side inlet (right/left) Ø 3/8" (19mm)
- Dynamic water pressure 0,1 - 10 bar
- 420 mm bowl height (w/out seat)
- Space saving (compared to traditional external macerator). Installed dimensions: 635 x 370 x 790 mm*
- 27 kg ceramic bowl weight, 13 kg ceramic cistern weight, 5,2 kg Macerator net weight
- Supralit WC seat & cover with Soft Close hinges
- Side covers to hide pipe connections

(* Recommended)



WARNING!

Other than toilet paper, don't throw inside the WC bowl anything that you haven't eaten first



MODELS / REFERENCES

Reference	Description		Comments
A34T0N2000	Pack	The GAP ROUND Floor Standing Toilet, Close-Coupled, BTW, Rimless, with built-in Macerator pump	Complete pack

This pack includes:

A3420N9..0	Bowl	WC FS CC 655 RIMLESS	Includes Roca rimless system & fixing kit to floor
A3410N4..0	Cistern	Cistern lateral inlet Ø 3/8"(19 mm) 4,5/3 L	Includes valve kit
A801D12..1	Seat & cover	Supralit, metal hinges, soft close	-
A818006000	Macerator Pump	D-Trit Macerator pump 400W	Includes flanges, hydraulic connectors, fixing kit to floor and side covers

RECOMMENDED ACCESSORIES

Reference	Description		Comments
A525164400	Angle valve	Ceramic angle valve 1/2"- 3/8"	-

STANDARDS

Meets the following standards

- EN 997 (CL1-5-VRII and CL2)
- EN 14124
- EN 12050-3
- EN 55014-1 EN 55014-2 (Electromagnetic Compatibility)
- EN 60335-1 EN 60335-2-84 (Safety of Household appliances)



